2

Serial No. 09/671,636 Customer ID: 25094

## IN THE CLAIMS:

Please amend the claims as follows:

- 1. (Currently Amended) A method of signal transmission, comprising overlapping a plurality of direct-sequence spread-spectrum signals using carrier frequencies that are orthogonally spaced relative to an integral multiple of a bit rate rather than a chip rate
- 2. **(Original)** A method of claim 1, further comprising common frequency-hopping encoding said plurality of direct-sequence spread-spectrum signals.
- (Original) The method of claim 1, further comprising individual, differential
   frequency-hopping encoding each of said plurality of direct-sequence spread-spectrum signals.
- 4. **(Original)** The method of claim 1, wherein the frequency-hopping modulation is performed in a continuous-phase manner.
- 5. (**Original**) The method of claim 1, further comprising time-hopping encoding said plurality of direct-sequence spread-spectrum signals.
- 6. (Original) The method of claim 5, further comprising frequency-hopping encoding said plurality of direct-sequence spread-spectrum signals.
- 7. (Original) The method of claim 1, wherein overlapping includes synchronously allocating each of a plurality of users to one of a plurality of orthogonal channels.

Gray Cary\AU\4124931.1 2500940-991300

Serial No. 09/671,636 Customer ID: 25094

3

- 8. (Currently Amended) The method of claim 1, wherein overlapping includes encoding a frequency shift in a subset of bits that compose define a code word.
- 9. (Currently Amended) The method of claim 1, wherein overlapping includes establishing a bit- clock synchronization; and

<u>further comprising</u> multiplying an incoming signal by an estimate of a desired signal; and integrating a product over an integral multiple of a bit period rather than a chip rate

- 10. (Original) The method of claim 1, further comprising retransmitting one of said plurality of direct-sequence spread-spectrum signals.
- 11. (Original) The method of claim 1, further comprising checking one of said plurality of direct-sequence spread-spectrum signals with an error-correcting code.

## 12-14. (Canceled)

15. (Currently Amended) A computer program, comprising computer- or machine-readable program elements translatable for implementing <u>a</u> the method of <u>claim 1 signal</u> transmission including overlapping a plurality of direct-sequence spread-spectrum signals using carrier frequencies that are orthogonally spaced relative to an integral multiple of a bit rate rather than a chip rate.

Gray Cary\AU\4124931.1 2500940-991300

Serial No. 09/671,636 Customer ID: 25094

4

16-24. (Canceled)

- 25. (Currently Amended) A computer program comprising computer program means adapted to perform the steps of overlapping a plurality of direct-sequence spread-spectrum signals using carrier frequencies that are orthogonally spaced relative to an integral multiple of a bit rate when said program is run on a computer rather than a chip rate
- 26. (**Original**) A computer program as claimed in claim 25, embodied on a computer-readable medium.
- 27. (Cancel)
- 28. (Currently Amended)

  A The method of claim 27 comprising, providing a directsequence spread-spectrum communication system that increases a number of users by utilizing
  a plurality of closely spaced orthogonal carriers that produce overlapping spectra, wherein a
  spacing of the plurality of orthogonal carriers is based on a symbol bit rate and not a chip rate.
- 29. **(Original)** The method of claim 28, further comprising frequency-hopping encoding the overlapping spectra.
- 30. (Original) The method of claim 28, further comprising time-hopping encoding the overlapping spectra.
- 31. (Original) The method of claim 30, further comprising frequency-hopping encoding the overlapping spectra.

Gray Cary\AU\4124931.1 2500940.991300

Tonk

5

Serial No. 09/671,636 Customer ID: 25094

32. (Currently Amended) A method of signal transmission, comprising overlapping a plurality of synchronous direct-sequence spread-spectrum signals using carrier fequencies that are orthogonally spaced relative to integral sub-multiples of at least one bit rate rather than a chip rate.

- 33. (Original) The method of claim 32 wherein the plurality of synchronous direct-sequence spread-spectrum signals are overlapped relative to an integral sub-multiple of a common bit rate.
- 34. (Currently Amended) A method of signal transmission, comprising overlapping a plurality of synchronous direct-sequence spread-spectrum signals using carrier frequencies that are orthogonally spaced relative to one-half of a bit rate rather than a chip rate.